



## 5HN9-OG

90° 弯公制外螺纹可调向柱  
 端轻系列 ISO 6149-3/NPT 内螺纹  
 90° ELBOW METIRC MALE ADJUSTABLE STUD  
 END L-SERIES ISO 6149-3/ NPT FEMALE

代号 PART NO.	螺纹 THREAD		O 形圈 O-RING		尺寸 DIMENSIONS				
	E	F	E 端		A	B	S1	S2	
5HN9-10-02OG	M10X1	Z1/8"X27	8.1X1.6		28.8	17.8	14	14	
5HN9-12-02OG	M12X1.5	Z1/8"X27	9.3X2.4		34	17.8	16	17	
5HN9-12-04OG	M12X1.5	Z1/4"X18	9.3X2.4		35.5	22.4	19	17	
5HN9-14-04OG	M14X1.5	Z1/4"X18	11.3X2.4		35.5	22.4	19	19	
5HN9-16-06OG	M16X1.5	Z3/8"X18	13.3X2.4		40.2	25	22	22	
5HN9-16-08OG	M16X1.5	Z1/2"X14	13.3X2.4		43	31.2	30	22	
5HN9-18-06OG	M18X1.5	Z3/8"X18	15.3X2.4		40.5	25	24	24	
5HN9-18-08OG	M18X1.5	Z1/2"X14	15.3X2.4		44	31.2	30	24	
5HN9-22-02OG	M22X1.5	Z1/8"X27	19.3X2.4		40.2	22	22	27	
5HN9-22-06OG	M22X1.5	Z3/8"X18	19.3X2.4		41.5	25	24	27	
5HN9-22-08OG	M22X1.5	Z1/2"X14	19.3X2.4		45	31.2	30	27	
5HN9-26-12OG	M26X1.5	Z3/4"X14	23.5X3		52	34.5	33	32	
5HN9-27-12OG	M27X2	Z3/4"X14	23.5X3		52	34.5	33	32	
5HN9-33-16OG	M33X2	Z1"X11.5	29.2X3		57.2	41.1	41	41	
5HN9-42-20OG	M42X2	Z1.1/4"X11.5	38.5X3		61.2	43.2	48	50	
5HN9-48-24OG	M48X2	Z1.1/2"X11.5	44.5X3		73	52.8	63	55	

注: E 端与 ISO 9974-1 油口相配, 去掉挡圈则与 ISO 6149-1 油口相配。      Note: E end is connected with ISO 9974-1 port and connected with ISO 6149-1 port without retaining ring.